
This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS							
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED		
1		RELEASED FOR PRODUCTION.	11/3/2016	DPD	JAG		




<u>NOTE:</u> ¬REF. AIRBUS T/N: RBEM632V3013101.

		1									
ASSY QTY	ASSY QTY	B/O	Part #	UNIT QTY	Description	Material	B/O INFORMATION OR SPECIFICATIONS	PG.		_	
			-1	1	SHIM	WHITE NYLON		2			4
	Χ		-3	1	LOCK WRENCH			3	TITLE		
	1		-5		ROD	1018/1020 CR		4	SERVO	D-COI	NTR
	1		-7		COVER	6061		5	DWG NO.		- 1
			-9	1	PLACARD	PLASTIC		6		KR	EM
		В/О	-11	1	SHORT STRAP	NYLON	(OLYMPIC SYNTHETICS)	7	MAT'L		
		В/О	-13	1	LONG STRAP	NYLON	(OLYMPIC SYNTHETICS)	8	HEAT TREAT FINISH		
	1	B/O	-15		SPRING PIN	STEEL	M3 X 22mm (MCMASTER-CARR #91611A160)	_	SPEC		
		B/O	-17	1	BOTTOM FOAM	ETHAFOAM 220, BLACK	5.79 X 11.26 X 20.12 (CASE SOLUTIONS)	9	DRAWN BY:	DUERFI	ELDT
		B/O	-19	1	TOP TOOL CUSHION	ETHAFOAM 220, BLACK	1.79 X 11.26 X 20.12 (CASE SOLUTIONS)	10	CHECKED:	CLOUG	Н
		B/O	-21	1	CASE	PLASTIC	PELICAN #APP-1510-E	N/S	OPPS APPR:	ANDER	
		B/O		1	PLACARD	ALUMINUM	RB41011	N/S	QA APPR:	LINDSA	
	V224								APPROVED:	GILBER	
	ASSY -3								SCALE	1:8	DATE

ROL FITTINGS NUT GUIDE

	DWG NO.	חחם	- > 4 / /	32V3013101						
		KRI	=1/1/6	V3013	1					
	MAT'L				UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES					
	HEAT TREAT FINISH				.XXX ± .005	FRACTIONS ± 1/8				
					.XX ± .01 ANGLES ± .5° .X ± .1 SURFACES = 125/					
_	SPEC			1. BREAK AL	V					
	DRAWN BY:	DUERFE	LDT	.015 x 45° OR .015R 2. DIMENSIONAL LIMITS APPLY						
)	CHECKED:	CLOUGH	1		AFTER PLATING 3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009					
S	OPPS APPR:	ANDERS	SON							
S	QA APPR:	LINDSAY	/		USED ON MODEL					
J	APPROVED:	GILBERT			H175					
	SCALE	1:8 DATE 6/				SHEET 1 OF	10			



REVISIONS This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR. INITIAL APPROVED REV ECR DESCRIPTION DATE SERVO-CONTROL FITTINGS NUT GUIDE DWG NO. RBEM632V3013101-3 MAT'L UNLESS OTHERWISE SPECIFIED SURFACES = 125/ SPEC A T.I.


1. BREAK ALL SHARP EDGES


.015 x 45° OR .015R


2. DIMENSIONAL LIMITS APPLY
AFTER PLATING
3. INTERPRET DIM AND TOL PER
ASME Y14.5M-2009 DRAWN BY: DUERFELDT CHECKED: CLOUGH OPPS APPR: (-3) ANDERSON QA APPR: USED ON MODEL LINDSAY APPROVED: GILBERT H175 LOCK WRENCH SCALE 6/14/2016 SHEET 3 OF 10 1:4

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS							
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED		







NOTES:

1. DUAL FINISH:

1ST: ZINC PLATE, ASTM B633 TYPE I SC2. 2ND: POWDER COAT YELLOW, FED #13538.

NO POWDER COAT THIS SURFACE.



SERVO-CONTROL FITTINGS NUT GUIDE

RBEM632V3013101-5 MAT'L 1018/1020 CR HEAT TREAT FINISH SEE NOTE 1 SPEC DRAWN BY: DUERFELDT CHECKED: CLOUGH OPPS APPR: ANDERSON

DIMENSIONS ARE IN INCHES
.XXX ± .005 FRACTIONS ± 1/8
.XX ± .01 ANGLES ±.5° .XX ± .01 .X ± .1 SURFACES = 125/

UNLESS OTHERWISE SPECIFIED

1. BREAK ALL SHARP EDGES .015 x 45 'OR .015R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING 3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009


QA APPR: USED ON MODEL LINDSAY APPROVED: GILBERT H175 SCALE 1:2 6/14/2016 SHEET 4 OF 10


(-5)

ROD


This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.


		REVISIONS			
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED






COVER







TITLE SERVO-CONTROL FITTINGS NUT GUIDE

DWG NO. DDF A 4 (20) (20) 2101 7 REV

	KRE	M632V	30131	01-/	1		
MAT'L 6061			UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES				
HEAT TREAT			.XXX ± .005	FRACTIONS ± 1/8			
FINISH CLEAF	R ANODIZE			ANGLES ±.5° SURFACES = 1	25/		
SPEC MIL-A-	8625F, TYPE	II, CLASS I	1. BREAK AL	\overline{V}			
DRAWN BY:	DUERFE	LDT	.015 x 45° OR .015R 2. DIMENSIONAL LIMITS APPLY				
CHECKED:	CLOUGH		AFTER PLA				
OPPS APPR:	ANDERS	SON	ASME Y14.				
QA APPR:	LINDSAY	′	USED ON MODEL				
APPROVED:	GILBERT						
SCALE	1:1	DATE 6/1	4/2016	SHEET 5 OF	10		

